



Wiring Device-Kellems

Straight Blade Devices, Plug, Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15P, Black

By Hubbell Wiring Device-Kellems
Catalog # [HBL5266CBKST](#)

Straight Blade Devices, Plug, Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15P, Black

Features

- Spring termination for a faster and more secure terminal connection
- Ribbed housing is impact and chemical resistant
- Superior cord grip design protects terminations from excess strain
- Accepts #14 - #10AWG, solid or stranded

General

Color	Black
Cord Range	0.230"-0.720"(5.8-18.3)
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	0.5
Insulation	Insulated Body
Item Type	Insulgrip® Plug
Material	Nylon
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum without Impact -40 °C
Performance	<ul style="list-style-type: none">• Electrical - Current Interrupting - Certified for current interrupting at full rated current• Electrical - Dielectric Voltage - Withstands 2,000V minimum• Environmental - Flammability - UL 94 V-2• Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)• Mechanical - Product Identification - Ratings are a permanent part of the device• Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only• Mechanical - Terminal

Dimensions

Display Size	Standard Sized Product
Weight	0.2 lb

Electrical Ratings

Connectivity	Spring Termination
Current / Amperage Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 V

Conductor Related

Conductor Range	#14 AWG to #10 AWG
Cord Type	All Listed Portables
Number Of Conductors	3-Wire Grounding
Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Certifications and Compliance

Industry Standard(s)	<ul style="list-style-type: none">• CSA Certified to C22.2 No. 42 File 280• Fed. Spec. W-C596G• NEMA® WD-6 Compliant
Nema Rating	5-15P

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Installation Manuals - PD3057](#)
[Sales Drawings - M14563](#)
[Warranty - Industrial & Commercial Products](#)

Related Products

[HBL5269CST - Straight Blade Devices, Connector, Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Black and White](#)

Identification - Terminals
identified in accordance
with UL 498 and CSA

Series	Insulgrip®
Size	3.28 in x 1.41 in x 1.09 in
Style	Standard
Temperature Rating	Maximum continuous 75°C; minimum -40°C (w/o impact)
Type	Plugs
UPC	783585964782



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
WDK-HBL5266CBKST-SPEC-EN | REV 1/2024