SEETRONIC

Product Data Sheet

Product Type **RJ45 Adapter**

Product Model **SE8FF-02-C6A**

Customer Name

Manufacturer	Prepared	Checked	Approved

Customer	Received	Checked	Confirmed

Distributor:

Techni-Lux

Phone: 407-857-8770
Fax: 407-857-8771
Email: sales@techni-lux.com
www.techni-lux.com

www.seetronic.com

SEETRONIC

Product Data Sheet

Product Type	**RJ45 Adapter**
Product Model	**SE8FF-02-C6A**

Product Features

➢ RJ45 feedthrough coupler for linking cables, CAT6a, PoE++
➢ Accommodates SE8MC-02-NEW
➢ Shorter length and more exquisite compact design
➢ Complies with CAT6a according to TIA / EIA 568B and ISO / IEC 11801 standard
➢ Very lightweight, fast and stable signal transmission

SEETRONIC

Product Parameters

Item	Specification
Connection type	Adapter

Electrical Parameters

Item	Specification
Contact resistance	< 10 mΩ
Rated current	2 A
Rated voltage	60 V
Insulation resistance	≥ 0.5GΩ
Dielectric strength	1 KV DC
Frequencyrange	1~100 MHz
Transmission performance	CAT6a
Ethernet power supply	PoE++ accdg. IEEE 802.3bt

SEETRONIC

Mechanical Parameters

Item	Specification
Insertion force	≤ 20 N
Service life	> 1000 mating cycles
Locking device	Latch lock

Material and Environmental Parameters

Item	Specification
Contacts	Copper alloy
Insert	PBT
Contact surface	Au
Panel	Zinc alloy
Temperature range	-30°C ~ +80°C
Protection degree	IP65

Standards and Certifications

Standards	TIA/EIA 586B, IEC11801

SEETRONIC

Product Drawing

28.00±0.50

PUSH

CAT6A

SEETRONIC

33.10±0.50

(55.15)

(45.95)

(37.70)

SE8FF-02-C6A
Adapter

Unit: mm

SEETRONIC

Packaging Method

PE bag packing, 1 pc per bag

50 pcs per inner carton, 5 inner cartons per master carton (250 pcs per master carton)

Accessory

☑ No accessories   ☐ Back fastener plate

☐ Screws   ☐ Waterproof gasket