

HMI STUDIO 800W



Product features and benefits

- HMI technology that offers highly efficient, warm-white color without the use of CTO filters
- Reduced flicker when used with high-speed electronic ballasts (up to 1000 Hz and higher)
- Suited for both analog and digital film productions
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only 1°K/hr
- Dimmable down to 40% with stable color using many electronic ballasts
- High energy efficiency providing up to 100 LPW
- Enhanced safety with UV-Stop (UVS) feature on all STUDIO types

Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	55179			
Product Name	HMISTUDIO800W 10/CS 1/SKU			
Ordering Abbreviation	HMI STUDIO 800W			
Brand Name	OSRAM			
General Description	Metal Halide, 800 watt, 3200K CCT, G22 base			
Application	Film, TV & Video Production, Photography			
Product Remark	 Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius. UVS=UV-Stop. UVS technology reduces harmful UV-B and UV-C ultraviolet radiation emissions by 99%. Designed to approximate tungsten color temperature (2800K to 3400K) inside of a fixture. Note that color temperature will vary based on the ballast used and its operating frequency. 			

Electrical data

Nominal Wattage	800 W
Nominal Voltage	97 V
Current (A)	AC A
Type of Current	AC

Light technical data

Luminous Flux	47300 lm
Light Center Length - LCL (mm)	70 mm
Color Temperature	3850 K
Average Rated Life	1000 h

Physical attributes

Base	G22 Medium Bipost		
Bulb Shape	T9.5		
Maximum Overall Length (mm)	145 mm		
Length I (mm)	145 mm		
Diameter d (mm)	30.00 mm		
Distance a (mm)	70 mm		
Electrode Gap - cold (mm)	7 mm		

Product datasheet

Additional product data

Operating Position	Any
Cooling	Convection
Hot Restart	Yes

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
55179	4052899984417	Folding box (SKU)	1		
55179	4052899984424	Shipping box (Case)	10	11.6 in x 4.9 in x 7.5 in	3.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.

Phone: 407-857-8770 Fax: 407-857-8771 Email: sales@techni-lux.com www.techni-lux.com