Product datasheet



HRI 132 W

SIRIUS HRI | Metal halide lamps



Areas of application

- Perfect for small and lightweight moving heads

Product benefits

- High luminance due to very short arc and high internal pressure
- Bright light for brilliant light effects
- Long lifetime
- Lightweight and compact reflector lamps with ECG
- Optimized burner design allows any burning position
- Easy relamping
- Uniform light output throughout the entire lifetime



April 27, 2015, 16:10:25 HRI 132 W

Product datasheet

Technical data


Electrical data

Nominal wattage	132 W
Nominal current	1.9 A

Photometrical data

Luminous flux	5150 lm
Color temperature	9200 К
Color rendering index Ra	60

Dimensions & weight



Diameter	46.0 mm
Length	42.0 mm
Arc length	1.0 mm
Lifespan	
Lifespan	6000 h
Capabilities	

Burning position

Any

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899028708	HRI 132 W	Folding carton box 1	- x - x -		
4052899028715	HRI 132 W	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm ³	255.00 g
4052899028722	HRI 132 W	Shipping carton box 20	- x - x -		

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Distributor:



Phone: 407-857-8770 Fax: 407-857-8771 Email: sales@techni-lux.com