

Product data

General Characteristics

System Description MiniFastFit
Cap-Base PGJX36
Cap-Base Information PGJX36
Execution Operating Position any
Main Application Entertainment
Life to 50% failures 750 hr

• Light Technical Characteristics

-
81 Ra8
6000 K
6000 K
0.321 -
0.327 -
83000 Lm
83 Lm/W

• Electrical Characteristics

Lamp VVattage	1000 VV
Lamp Wattage Tech-	1000.0 W
nical	
Lamp Current	11.1 A
Ignition Supply	198 (min) V
Voltage	

MSR Gold™ MiniFastFit (Touring/Stage)

MSR Gold™ 1000 MiniFastFit

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity. Moreover, the latest addition to the range: PhilipsMSR Gold™1000 FastFit offers a pure, white light (6000K). Especially designed for theater applications.

Dimmable No

Luminaire Design Requirements

Pinch Temperature 500 (max) C Bulb Temperature 950 (max) C

• Product Dimensions

 Overall Length C
 112 (max) mm

 Diameter D
 26 (max) mm

 Width F
 35.3 (min), 36 (nom), 36.5 (max) mm

 Light Center Length L
 55 (min), 56 (nom), 57 (max) mm

Arc Length O 5.5 mm

• Product Data


Order code 928171405112 928171405112 Full product code MSR Gold™ 1000 MiniFastFit Full product name MSR Gold 1000 MiniFastFit Order product name Pieces per pack Packing configuration Packs per outerbox 63 8718291785125 Bar code on pack -EAN1 8718291785125 Bar code on outerbox - EAN3 928171405112 Logistic code(s) -12NC

Net weight per piece 0.055 kg




MSR Gold™ MiniFastFit (Touring/Stage)

Dimensional drawing



MSR Gold™ 1000 MiniFastFit

Product	A (Min)	A (Norm)	A (Max)	C (Max)	D (Max)	D1 (Norm)	F (Min)	F (Norm)	F (Max)	L (Min)	L (Norm)	L (Max)	O (Norm)
MSR GOLD 1000 MiniFastFit	-	-	-	112	26	-	35.3	36	36.5	55	56	57	5.5





© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

Distributor:



2014, June 21 data subject to change